



**INDUSTRIES SERVED**



**CHOCOLATE & CANDY**



**MEAT & POULTRY**



**DRESSINGS, RELISHES & DIPS**



**SOUPS & SAUCES**



**CHEESE & DAIRY**



**PET FOOD**



**SAVOURY & PIE FILLINGS**



**READY MEALS**

CM Process Solutions range of pneumatically controlled Euro Buggy Scales are used in the food production industry to weigh ingredients within a standard 400 & 600lb DIN 9797 Euro style buggy.

Fully 304 grade stainless steel construction, available as a free standard unit or mobile design eliminating the need for floor pits or ramps.

**FEATURES**

**304**  
 STAINLESS  
 STEEL

**400lb** **600lb**  
 FITS BOTH

**200lbs**  
 Mettler Toledo  
 WEIGH HEAD  
 OPTIONS

**QUICK  
 LEVELLING**

**IP65**  
 WATERPROOF

**775lb**  
 MAX CAPACITY

**S. STEEL  
 CYLINDER**

**HYGIENIC  
 BY DESIGN**



## PNEUMATICALLY CONTROLLED STATIC EURO BUGGY WEIGH SCALES



### OPERATIONAL DESIGN

CM Process Solutions range of Euro Buggy Scales are used in the food production industry to weigh ingredients within a standard 400 & 600lb DIN 9797 Euro style buggy.

The scale is pneumatically controlled and has a capacity of 772lbs, it can be supplied on adjustable legs or mobile, it improves health & safety within the workplace by removing the need to push a buggy up a hazardous ramp with the potential for slips and trips.

The crevice free design allows quick and easy clean down in place. Unlike a floor scale which needs to be completely removed to clean on the underside.



sales@cmpsolutions.net  
t. 951 808 4376 f. 951 808 8657

[View this product online](#)

### METTLER TOLEDO DISPLAY HEAD

The weigh scale incorporates a stainless-steel load cell and Mettler Toledo IND236 display head.



<b>DIMENSIONS</b>	220 x 150 x 93.3mm
<b>POWER</b>	85VAC - 246VAC 50 - 60HZ
<b>SCALE INTERFACE</b>	1 Analogue Up to 4 350HM Loadcells
<b>SCALE RESOLUTION</b>	Up to 30,000 scale divisions can be configured
<b>EXCITATION VOLT</b>	5VDC
<b>UNITS</b>	G, KG, LB, OZ
<b>KEYPAD</b>	Zero, Tare, Clear, On/Off, Print, F1 & F2
<b>COMMUNICATION</b>	COM1 RS232 as standard COM2 RS232 / RS422 / RS485 configurable with digital IO as option
<b>FIELDBUS CONNECTIVITY</b>	None
<b>INTEGRATED APPLICATIONS</b>	Weighing Over/Under. Check weighing with 10 records

